(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 7 October 2004 (07.10.2004)

PCT

(10) International Publication Number WO 2004/085326 A1

(51) International Patent Classification⁷: C03B 27/044

(21) International Application Number:

PCT/GB2004/001263

- (22) International Filing Date: 25 March 2004 (25.03.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03425197.5


28 March 2003 (28.03.2003) El

- (71) Applicant (for all designated States except US): PILK-INGTON PLC [GB/GB]; Prescot Road, St. Helens, Merseyside WA10 3TT (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): CARLOMAGNO, Giovanni, Maria [IT/IT]; Via Scarlatti, 32, I- 80129 Napoli (IT).

- (74) Agents: HALLIWELL, Anthony, Charles et al.; Group Intellectual Property Department, Pilkington plc, Pilkington European Technical Centre, Hall Lane, Lathom, Ormskirk, Lancashire L40 5UF (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: TEMPERING BENT GLASS SHEETS



(57) Abstract: An apparatus (16) for tempering a bent glass sheet (11) is disclosed. The apparatus comprises a means (19) of conveying the sheet through the apparatus and a pair of blastheads (20, 21) for quenching the sheet with quench gas. Each blasthead comprises a plurality of spaced elongate plenums (22) for supplying quench gas to an array (40) of quench nozzles (23, 92), the nozzles being mutually inclined to provide diverging jets of quench gas. The plenums extend transversely to the direction of conveyance of the sheet, and the array of nozzles is curved in at least one direction. The array may comprise rows of nozzles extending along lines which are curved in the direction of elongation of the plenums; preferably the curvature of the rows matches the average local curvature of the bent glass sheet in the corresponding direction. Also disclosed is a production line (10) incorporating the apparatus (16).

WO 2004/085326 A1



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report